



Professional In Human Machine Interface




Highest Standards · Aesthetic Appeal · Sturdy Aluminum Casing

- The high-speed 600/800 MHz microprocessor has an outstanding data processing architecture that enhances communication throughput and graphic display functionality to perform complicated animations and multi-page switching without delay
- Employs a sturdy aluminum casing
- Vivid screens including a new 12" 1024 by 768 pixel TFT display
- CANopen protocol support
- Isolation in 24VDC input
- Isolation in RS485/CAN bus
- Accurate and reliable touchscreens with a guaranteed lifespan of one million continuous key presses
- Industrial-Grade construction
- Aesthetically appealing

□ Enhanced Account Management

- Add/Delete Accounts
- Modify Privileges
- Reset Passwords



□ Extended User Accounts and Access Levels

- Extended user accounts (128)
- Extended access levels (14)



□ USB Security Key

Now you can assign access levels for specific periods of time



2. Restrict access to some operations in the HMI with the USB security key

Assign access levels for specific periods of time

Assign different access levels for objects or features to enhance security control




□ Powerful Connectivity



□ Powerful Macro Editor and Commands

- Macro syntax is similar to VB-Script. Users can use Macros to design the desired additional features.
- Powerful Macro commands support user defined protocols (free protocol) for other communication devices.
- Sophisticated features are designed for processing complex expressions and string manipulation. This enhances the communication between users and projects.
- The new Macro editing window with toolbars makes designing Macros extremely easy.
- Supports the creation of user-defined Macro Libraries. This feature allows Macro Libraries to be used in future HMI project designs.




□ Use Label Tags to Display Multiple Languages

Label Tag Library a spreadsheet-like display for inputting text in different languages for application in a project. Export Label Tags in CSV format to Excel for editing. Language contents can then be edited further and imported to the Label Tag table.



□ Address Tag

1. Get Tag Information
2. Edit Project with Tag Name
3. Download Project to HMI
4. Communication via Tag Name




□ E-mail Notification

Inform personnel via E-mail when alarms occur




□ EasyWatch

A powerful tool for monitoring and modifying specific address values of remote HMI and PLC devices.




□ EasyDiagnoser

The EasyDiagnoser utility helps you to analyze and detect communications between the HMI and PLC.



□ Easy Access

Via the innovative EasyAccess feature, you can easily manage your eMT3000 Series HMI on a network.



□ Account Management and E-mail Configuration via Administrator Tools



□ EasySimulator

During or after project programming, you can execute an Online Simulation on a PC by directly connecting it to your with PLC (10 min limit) or perform an Offline Simulation without the PLC.

- Offline Simulator




- Online Simulator






Model		eMT3070B	eMT3105P	eMT3120A	eMT3150A
Display	Display	7" TFT	10.4" TFT	12.1" TFT	15" TFT
	Resolution	800x480	800x600	1024x768	1024x768
	Brightness (cd/m ²)	500	400	500	400
	Contrast Ratio	500:1	400:1	700:1	700:1
	Backlight Type	LED	LED	LED	LED
	Backlight Life Time	>30,000 hrs.	>30,000 hrs.	>50,000 hrs.	>50,000 hrs.
	Colors	16.7M	262K	16.2M	16.2M
	LCD Viewing Angle (T/B/L/R)	60 / 50 / 65 / 65	60 / 70 / 70 / 70	80 / 80 / 80 / 80	70 / 70 / 80 / 80
Touch Panel	Type	4-wire Resistive Type	4-wire Resistive Type	4-wire Resistive Type	4-wire Resistive Type
	Accuracy	Active Area Length(X)±2%, Width(Y)±2%	Active Area Length(X)±2%, Width(Y)±2%	Active Area Length(X)±2%, Width(Y)±2%	Active Area Length(X)±2%, Width(Y)±2%
Memory	Flash	256 MB	256 MB	256 MB	256 MB
Processor		32Bit RISC Cortex-A8 1GHz	32Bit RISC CPU 800MHz	32Bit RISC CPU 800MHz	32Bit RISC CPU 800MHz
I/O Port	SD Card Slot	SD/SDHC	SD/SDHC	SD/SDHC	SD/SDHC
	USB Host	USB 2.0 x 1	USB 2.0 x 1	USB 2.0 x 1	USB 2.0 x 1
	USB Client	USB 2.0 x 1 (Micro USB)	USB 2.0 x 1	USB 2.0 x 1	USB 2.0 x 1
	Ethernet	10/100 Base-T x 1	10/100 Base-T x 1	10/100 Base-T x 1	10/100 Base-T x 1
	COM Port	COM1: RS-232/RS-485 2W/4W COM3: RS-232/RS-485 2W*	COM1: RS-232/RS-485 2W/4W COM3: RS-232/RS-485 2W*	COM1: RS-232/RS-485 2W/4W COM3: RS-232/RS-485 2W*	COM1: RS-232/RS-485 2W/4W COM3: RS-232/RS-485 2W*
	RS-485 Dual Isolation	Yes	Yes	Yes	Yes
	CAN Bus	Yes	Yes	Yes	Yes
		Built-in	Built-in	Built-in	Built-in
RTC	Input Power	24±20% VDC	24±20%VDC	24±20%VDC	24±20%VDC
	Power Isolation	Built-in	Built-in	Built-in	Built-in
	Power Consumption	400mA@24VDC	800mA@24VDC	850mA@24VDC	900mA@24VDC
	Voltage Resistance	500VAC (1 min.)	500VAC (1 min.)	500VAC (1 min.)	500VAC (1 min.)
	Isolation Resistance	Exceed 50MΩ at 500VDC	Exceed 50MΩ at 500VDC	Exceed 50MΩ at 500VDC	Exceed 50MΩ at 500VDC
	Vibration Endurance	10 to 25Hz (X, Y, Z direction 2G 30 minutes)	10 to 25Hz (X, Y, Z direction 2G 30 minutes)	10 to 25Hz (X, Y, Z direction 2G 30 minutes)	10 to 25Hz (X, Y, Z direction 2G 30 minutes)
		Yes	Yes	Yes	Yes
		Aluminum	Plastic	Aluminum	Aluminum
Specification	Dimensions WxHxD	200.3 x 146.3 x 42.5 mm	286.2 x 212.8 x 50 mm	317 x 244 x 46 mm	366 x 293 x 57 mm
	Panel Cutout	192 x 138 mm	259 x 201 mm	305 x 231 mm	352 x 279 mm
	Weight	Approx 0.9kg	Approx 1.6kg	Approx 2.1kg	Approx 2.75kg
	Mount	Panel mount	Panel mount, VESA mount 75 x 75 mm	Panel mount, VESA mount 75 x 75 mm	Panel mount, VESA mount 75 x 75 mm
		UL Type 4X (indoor use only) / NEMA4 / IP66 Compliant Front Panel	UL Type 4X (indoor use only) / NEMA4 / IP65 Compliant Front Panel	NEMA 4 / IP66 Compliant Front Panel	UL Type 4X (indoor use only) / NEMA4 / IP65 Compliant Front Panel
		-20°~70°C (-4°~158°F)	-20°~60°C (-4°~140°F)	-20°~70°C (-4°~158°F)	-20°~70°C (-4°~158°F)
Environment	Operating Temperature	-20°~50°C (-4°~122°F)	0°~50°C (32°~122°F)	0°~50°C (32°~122°F)	0°~50°C (32°~122°F)
	Relative Humidity	10% ~ 90% (non-condensing)	10% ~ 90% (non-condensing)	10% ~ 90% (non-condensing)	10% ~ 90% (non-condensing)
	CE	CE marked	CE marked	CE marked	CE marked
	UL	cULus Listed	cULus Listed	cULus Listed	cULus Listed
Software		EasyBuilder Pro	EasyBuilder Pro	EasyBuilder Pro	EasyBuilder Pro


* Only Tx & Rx (no RTS/CTS) may be used for COM1 RS-232 when COM3 RS-232 is also used.

eMT3070B


Front View




Rear View




Bottom View




Panel Cutout

eMT3105P


Front View




Rear View




Bottom View




Panel Cutout

eMT3120A


Front View




Rear View




Bottom View




Panel Cutout

eMT3150A

Front View



Rear View



Panel Cutout



WEINTEK LABS., INC.
Taiwan



For information, sales & support contact:
www.switchesunlimited.com □ sales@switchesunlimited.com
Phone: 800-221-0487 □ Fax: 718-672-6370



ISO 9001: 2015

English | Sep 2017